

## LOAD LIMITER SETTING 勸告置

POWER SOURCE AC 3Φ 50Hz

POWER SOURCE (V)	HOIST 規格 (TON)	MOTOR 容量 Kw x P	MOTOR CURRENT ( A )		LOAD LIMITER SETTING置			CURRENT TRANSFORMER SPEC				
			100%負荷時	110%負荷時	負荷電流 %	作動時間 (SEC)	SHOCK時間 (SEC)	MODEL	貫通回數 (TURN)	連結 方式	1次測電流 (A)	2次測電流 (A)
220V	1S 1.9W 2W	2.0/0.5 x 2/8	8.6/3.6A	9.2/4A	110	1	1	CT-1	1	K-1	50	5
380V	1S 1.9W 2W	2.0/0.5 x 2/8	4/2A	4.8/2.2A	110	1	1	CT-1	1	K-1	50	5
440V	1S 1.9W 2W	2.0/0.5 x 2/8	3.6/1.8A	4/2A	110	1	1	CT-1	1	K-1	50	5
460V	1S 1.9W 2W	2.0/0.5 x 2/8	3.4/1.7A	3.8/1.9A	110	1	1	CT-1	1	K-1	50	5
480V	1S 1.9W 2W	2.0/0.5 x 2/8	3.3/1.6A	3.6/1.8A	110	1	1	CT-1	1	K-1	50	5

☞ 제품의 성능향상을 위하여 권고치가 다소 변동이 될 수 있음.